




# Turbo-Centrifuge AZF-T15

Automatic discharge

Automatic Cleaning coolants and other Liquids without Filter media



Technical Information	
Flowrate	1 to 80 LPM
Medium	Oil and Emulsion
PH	6.5 until 9.5 / 6.5 until 10.0 / 4.0 until 14.0
Temperature	60° C
Quality of cleanliness	Down to 1 µm possible
Material Housing	Steel / Stainless Steel
Material Rotor	Aluminium / Aluminium anodized / Stainless Steel
Rotor capacity	15 dm <sup>3</sup>
Sludge Volume	5 kg / hour
Type of cleaning	2 phase
Rotor Speed	3000 UPM
Separating Factor	1550 g (1 g = gravity acceleration)
Noise emission	< 78 dBa
Drive	Directdrive (Frequency controlled)
Drive Power	3 kW
Solids discharge	Automatically
Liquid return	Under pressure
Controlpanel	Including
Inlet	Feed Pump needed
Dimension	> 870 x 820 x 870 mm
Weight	> 180 kg
Options	Inlet Tank (dirty liquid) Clean liquid Tank Pumps Chiller / Heating System / Aircleaner Magnetic Prefilter



**Turbo-Separator**  
a Turbo-International company

Turbo-Separator AG  
Bleikenstrasse 48  
9630 Wattwil  
Switzerland  
+41 71 987 70 20  
+41 71 987 20 29  
www.turbo-separator.ch  
info@turbo-separator.ch