




Turbo-Centrifuge AZF-T60

Automatic discharge

Suitable for separating particles from all sorts of industrial fluids



Technical Information	
Flowrate	1 to 300 LPM
Medium	Oil and Emulsion
PH	Standard from 6.5 to 9.5
Temperature	60° C / 90° C
Quality of cleanliness	Down to 1 µm possible
Material Housing	Steel / Stainless Steel
Material Rotor	Alu / Alu elox.
Rotor capacity	55 dm3
Sludge Volume	< 30 kg / hour
Type of cleaning	2 phase
Rotor Speed	2150 RPM to 2400 RPM
Separating Factor	1300 to 1630 g (1 g = gravity acceleration)
Noise emission	< 75 dBa possible
Drive	Belt Drive (Frequency controlled)
Drive Power	9.2 to 11 kW
Solids discharge	Automatically
Liquid return	Under pressure
Controlpanel	Including
Inlet	Need a Feedpump
Dimension	> 800 x 1200 x 1300 mm
Weight	> 650 kg
Options	Inlet (dirty liquid) Tank Clean Liquid Tank Pumps Chiller / Heating System / Aircleaner Magnetic Prefilter



Turbo-Separator
a Turbo-International company

Turbo-Separator AG
Bleikenstrasse 48
9630 Wattwil
Switzerland
+41 71 987 70 20
+41 71 987 20 29
www.turbo-separator.ch
info@turbo-separator.ch