




# Turbo-Centrifuge MZF-T14

Suitable for separating particles and tramp oil from all sorts of industrial fluids



Technical Information	
Flowrate	1 to 150 LPM
Medium	Oil and Emulsion
PH	6.5 until 9.5 / 6.5 until 10.0 / 4.0 until 14.0
Temperature	60° C / 90° C
Quality of cleanliness	Down to 1 µm possible
Material Housing	Steel or Stainless Steel
Material Rotor	Aluminium / Aluminium anodized / Stainless Steel
Rotor capacity	14 dm <sup>3</sup>
Sludge Volume	6 bis 10 kg
Type of cleaning	2 phase or 3 phase
Rotor Speed	2850 RPM to 3400 RPM
Separating Factor	1440 g to 2480 g (1 g = gravity acceleration)
Noise emission	< 75 dBa
Drive	Directdrive (Frequency controlled)
Drive Power	4.0 kW + 6 kW
Solids discharge	Manuell
Liquid return	Under pressure
Controlpanel	Including
Inlet	85 mm (self priming)
Dimension	> 550 x 680 x 880 mm
Weight	> 200 kg
Options	Inlet Tank (dirty liquid) Clean Liquid Tank Pumps Chiller / Heating System / Aircleaner Magnetic Prefilter

